

Gusto Drive Units

Introducing the Gusto 2000 series. As tough and reliable as the VC2000 drive units with our shortest lead times ever. The same peace of mind you've come to expect from our VC drive units is now available with the Gusto 2000 fast and 2000 slow drive units. Tested outdoors in Colorado's predictably unpredictable weather, with run times that would exhaust the best of us, Gusto has proven itself.



Gusto 2000 Vent Drive

FEATURES

- Gear motor: 115V / 1PH / 15HP / 120V; 60Hz; 2.5 amps - TEFCG
- Ball bearing motor with copper windings - Class B insulation
- Gear reducer: total reduction 1350:1; 1.2 and 2.68 RPM final output
- Output torque 2160 inch lb torque
- Lifts up to 325' of 4' polycarbonate roof ridge vent or 400' of 4' polycarbonate side vent
- Continuous duty
- 1-3/8" output coupling shaft

BENEFITS

- Thermal overload protection – automatic reset – continuous duty
- Quick reversing
- Worm gear with tapered roller bearings on dual output shafts immersed in synthetic oil
- Dual output shaft
- Sealed for life; limited or no maintenance required
- Superior heat dissipation through fin & casting design

Find out more



800.821.5829 sales@wadsworthcontrols.com
www.wadsworthcontrols.com

 **WADSWORTH**
Control Systems